





SECOND FLOOR PLAN

A1 SCALE : 1 : 125
 A3 SCALE : 1 : 250

*** ALL TOILETS:**

- ALL TOILETS FLOOR TO BE FINISHED W/ SELECTED HOMOGENEOUS FLOOR TILES
- ALL TOILETS WALL TO BE FINISHED W/ SELECTED GLAZED CERAMIC WALL TILES UP TO CEILING HEIGHT ALL ROUND INTERNAL WALL

LEGENDS:

- 100mm # UPVC W.P.
- 100mm # UPVC S.P.
- 100mm # UPVC V.P.
- 1 HOUR FIRE RATED DOOR
- 'KELLIAR' SIGN
- EMERGENCY LIGHT
- ABC 9 KG DRY POWDER FIRE EXTINGUISHER
- COMBINATION SMOKE HEAT DETECTOR
- SMOKE DETECTOR
- FIRE ALARM PANEL

ALL W.C.
 R.C. FLOOR SLAB SHALL BE WATERPROOFED AND EXTENDED UP 150mm MIN. TO ALL UPSTAIRS/WALL TO MANUF'S DETAIL AND SPECIFICATION. TO PROVIDE 100mm # S.S. FLOOR TRAP.

750MM X 750MM TRAP DOOR

STAIRCASE 2
 R.C STAIRCASE TO ENGR'S DETAILS W/ 20 RISERS, R=175MM, GONG=25MM, T=200MM W/ 1000MM HIGH M.S RAILING

STAIRCASE 1
 R.C STAIRCASE TO ENGR'S DETAILS W/ 20 RISERS, R=175MM, GONG=25MM, T=200MM W/ 1000MM HIGH M.S RAILING

130mm THK. BRICKWALL WITH CEMENT PLASTERED AND PAINTED FINISH ON BOTH SIDES

230mm THK. BRICKWALL WITH CEMENT PLASTERED AND PAINTED FINISH ON BOTH SIDES

NATURAL ANODIZED ALUMINIUM FRAME CASEMENT WINDOW WITH 5mm THK. MSG TINTED GLASS TO MANUF'S DETAIL

R.C. COLUMN TO ENGR'S DETAIL

DECORATIVE COLUMN TO ENGR'S DETAIL

R.C LEDGE TO ENGR'S DETAIL

A/C SCREENING TO MANUF'S DETAIL